



DELTA AR

AFS COOLANT 50% CONC.

Ready to use Coolant (Premixed with Water)

Product Description:

DELTA AR AFS COOLANT 50% CONC. based on Mono Ethylene Glycol (MEG) and suitable corrosion inhibitors to provide protection against frost and corrosion.

DELTA AR AFS COOLANT 50% CONC is fortified with anti-rust and anti-corrosion additives.

It has a very low freezing point and provides efficient heat transfer at high engine operating temperatures.

It is mixed with 50% of demineralized water for using as ready to use cooling and heat transfer fluid in internal combustion engines.

Features & Benefits:

- It is formulated to provide effective corrosion protection to cooling system and engine parts made out of ferrous and non-ferrous metals.
- Excellent protection of all hard metals in the cooling system and engine.
- It provides round the year protection against frost and boiling.
- It is compatible with seals.

Applications:

It is recommended for use in cooling systems of all types of liquid cooled automotive and industrial engines where such types of coolants are used. (Please refer OEM manual for recommended coolant).

Warning: Keep all antifreezes out of reach of children. Do not drink antifreeze. If swallowed, induce vomiting and immediately seek medical advice.

**KEY PROPERTIES:**

PROPERTIES	UNIT	Typical Values	Test Methods
Concentration		50%	
Specific Gravity @ 15 °C	kg/m ³	1060 - 1072	ASTM D-1122
Freezing Point (max.)	°C	-27	ASTM D-3321
Reflux Boiling Point (min.)	°C	107	ASTM D-1120
Reserve Alkalinity (min.)		8-9	ASTM D-1121
pH value		7 - 11	ASTM D-1287